


B 26/03/2020 changed max mm size of SAE 52 from 95mm into 96mm

Changed Product Marking

Α

24/03/2020

Date



DIMENSION TABLE MDCT Series Type SLF						
SAE Size	A1 inch	A2 inch	A1 Ø mm	A2 mm		
10	9/16	1 1/16	14	27		
12	11/16	1 1/4	17	32		
16	13/16	1 1/2	21	38		
20	13/16	1 3/4	21	44		
24	1 1/16	2	27	51		
28	1 5/16	2 1/4	33	57		
32	1 9/16	2 1/2	40	64		
36	1 13/16	2 3/4	46	70		
40	2 1/16	3	52	76		
44	2 5/16	3 1/4	59	83		
48	2 9/16	3 1/2	65	89		
52	2 13/16	3 3/4	71	96		

Description

Revision history




TORQUE VALUES				
Free Torque max.	Breaking Torque min.			
1Nm - 0.74 ft-lbf	10Nm - 7.38 ft-lbf			

PARTS LIST				
Item	Qty	Description		
1	1	Clamp Band 9/16" (D)		
2	1	Bottom Housing		
3	1	Top Housing		
4	1	Screw Hex Head 5/16" (H)		
5	8	Belleville Spring		

AVAILABLE MATERIALS						
Parts	Material ID AS1	Material ID AS2	Material ID AS3	Material ID AS4		
Screw	Steel, Zn plated	Stainless Steel AISI 410	300 Series	Stainless Steel AISI 316		
Housing	300 Series	300 Series	300 Series	Stainless Steel AISI 316		
Clamp Band	300 Series	300 Series	300 Series	Stainless Steel AISI 316		
Belleville Spring	300 Series	300 Series	300 Series	Stainless Steel AISI 304		

## Note(s):

- Dimensions and tolerances according to SAE J1508 Type SLF, four piece design.
- SAE Sizes not listed: The size is determined by A2 in inch 0.5 x 16, rounding to the nearest upper size in increment of 1.



MPC Clamps, Inc. - 3130 North Fry Road (Suite 500) - Katy, TX 77449 - United States - www.mpc-clamps.com